



patented

front-mount locking shown

Part Number	Rotation	Locking	Keyed (2 Keys/Lock)	Shaft Length	Shaft Style	Finish	Mount	Mounting Centers
3151	90° CW	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.500 [38.10]
3152	90° CC							
3154	90° CW	no	non-locking	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.750 [44.45]
3155	90° CC							
3251	90° CW	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.500 [38.10]
3252	90° CC							
3254	90° CW	no	non-locking	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.750 [44.45]
3255	90° CC							
3153	90° CW	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.750 [44.45]
315301	90° CC							
3157	90° CW	no	non-locking	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.750 [44.45]
315701	90° CC							
315304	360°	yes	CH751	4.00 [101.6]	non-threaded	chrome	front	1.750 [44.45]
315403	360°							
3253	90° CW	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.750 [44.45]
325301	90° CC							
3257	90° CW	no	non-locking	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.750 [44.45]
325701	90° CC							
3156	90° CW	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.813 [46.04]
315601	90° CC							
3159	90° CW	no	non-locking	4.00 [101.6]	3/8" - 24 thread	chrome	front	1.813 [46.04]
315901	90° CC							
3256	90° CW	yes	CH751	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.813 [46.04]
325601	90° CC							
3259	90° CW	no	non-locking	4.00 [101.6]	3/8" - 24 thread	chrome	blind	1.813 [46.04]
325901	90° CC							

- ▶ material: die cast zinc
- ▶ achieve NEMA 12 and IP64 enclosure access requirements when combined with escutcheon gasket sold separately, part no. **315G**
- ▶ meets ADA requirements
- ▶ includes dust shutter
- ▶ locking handles include (2) ringed keys
- ▶ front-mount handles do not include mounting screws (#10 recommended)
- ▶ blind-mount handles include (2) 8-32 x .25 [6.4] long mounting screws
- ▶ all handles include 3/8"-24 keps nuts